


LAMP PHOTOMETRIC REPORT

MODEL: 92EL62282030/WH		
POWER: 20W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 1955.2 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1205	1203	1203	1204	1207	1209	1209	1208	0- 10	117.3	117.3	6
20	1077	1072	1070	1072	1079	1084	1084	1082	10- 20	323.5	440.8	22.5
30	885.9	877.0	871.4	874.0	884.4	893.3	896.4	894.2	20- 30	454.9	895.6	45.8
40	548.2	538.3	533.9	538.8	551.8	561.7	563.9	559.3	30- 40	448.8	1344	68.8
50	261.5	252.7	248.7	251.8	261.4	270.1	272.7	270.2	40- 50	303.7	1648	84.3
60	121.1	117.4	114.2	115.6	119.6	123.7	125.1	124.8	50- 60	159.3	1807	92.4
70	68.65	63.90	59.89	64.05	68.11	69.24	67.46	69.62	60- 70	92.24	1900	97.2
80	26.17	21.62	18.64	22.21	25.01	24.87	22.74	25.18	70- 80	46.09	1946	99.5
90	0.4589	0.4515	0.4410	0.4578	0.4127	0.4025	0.3920	0.4019	80- 90	9.505	1955	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 06 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:


```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```