


LAMP PHOTOMETRIC REPORT

MODEL: 95Livial80/GR		
POWER: 15W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 495.75 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	292.7	298.9	291.1	295.1	299.7	294.1	300.8	296.4	0- 10	28.89	28.89	5.83
20	253.0	262.6	250.2	255.6	262.8	254.3	266.1	259.0	10- 20	78.49	107.4	21.7
30	198.0	208.4	195.5	200.4	207.1	198.7	211.6	204.2	20- 30	106.3	213.7	43.1
40	139.4	148.5	138.8	141.9	147.1	140.5	151.0	145.0	30- 40	108.2	321.9	64.9
50	79.94	85.97	79.13	81.60	85.68	81.89	89.17	84.33	40- 50	86.90	408.8	82.5
60	37.28	40.22	36.66	38.09	40.55	38.93	42.52	39.96	50- 60	53.24	462.0	93.2
70	13.17	14.03	12.84	13.53	14.56	14.25	15.44	14.27	60- 70	25.03	487.1	98.2
80	2.022	1.999	1.994	2.143	2.229	2.424	2.444	2.140	70- 80	7.649	494.7	99.8
90	0.0881	0.0865	0.0871	0.0853	0.0667	0.0730	0.0735	0.0660	80- 90	1.032	495.7	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 30 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```