


LAMP PHOTOMETRIC REPORT

MODEL: 95Livia90/GR		
POWER: 6W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 465.16 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	384.4	397.1	415.8	423.8	421.2	409.3	392.8	384.4	0- 10	40.92	40.92	8.8
20	274.4	288.8	309.1	320.9	317.6	297.6	283.8	277.8	10- 20	97.96	138.9	29.9
30	177.6	188.5	202.4	213.0	212.0	195.0	188.5	183.4	20- 30	111.4	250.3	53.8
40	106.0	115.3	124.9	128.7	129.2	122.1	116.6	111.5	30- 40	96.54	346.8	74.6
50	58.79	65.60	71.55	71.50	71.60	70.60	66.89	62.17	40- 50	70.36	417.2	89.7
60	28.99	32.93	36.19	35.58	35.39	35.31	33.05	30.23	50- 60	43.94	461.1	99.1
70	0	0	0	0	0	0	0	0	60- 70	4.016	465.2	100
80	0	0	0	0	0	0	0	0	70- 80	0	465.2	100
90	0	0	0	0	0	0	0	0	80- 90	0	465.2	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature:25.3°C
 Operators:
 Test Date:19 December 2022

γ Range: 0 - 60DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 60DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 60DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```