

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	5000.1 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	42.5V x 42.6H
	At 50% of Imax	17.2V x 17.3H
	At 90% of Imax	6.5V x 6.6H

Beam Flux	Total	921.8 lumens per klm.
	To 10% of Imax	603.2 lumens per klm.
	To 50% of Imax	259.5 lumens per klm.
	To 90% of Imax	33.5 lumens per klm.

Upward LOR	0.0 %
Downward LOR	92.2 %


Luminaire Efficiency (Light Output Ratio)	91.7 %
---	--------

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25.3°C
Operators:
Test Date: 24 January 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.340m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 96GRF1/315220W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 100 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	96GRF1/315220W	Imax (cd)	1150
NOMINAL POWER (W)	3	AVAILABILITY (%)	59.7
RATED VOLTAGE (V)	230	Avai. FLUX (lm)	137.4
NOMINAL FLUX (lm)	230	LOR (%)	91.7
LAMPS INSIDE	1	TOTAL FLUX (lm)	210.9
TEST VOLTAGE (V)	230	θ @50% (H,V)	17,17DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00
90	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.02	0.02	0.03	0.02	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.19	0.00
80	0.00	0.00	0.00	0.01	0.02	0.04	0.06	0.08	0.10	0.11	0.10	0.07	0.05	0.03	0.02	0.01	0.00	0.00	0.70	0.00
70	0.00	0.00	0.01	0.03	0.05	0.08	0.13	0.19	0.23	0.25	0.22	0.16	0.10	0.06	0.03	0.01	0.00	0.00	1.55	0.00
60	0.00	0.00	0.02	0.04	0.08	0.15	0.27	0.37	0.44	0.46	0.42	0.30	0.17	0.09	0.05	0.02	0.00	0.00	2.88	0.00
50	0.00	0.00	0.02	0.05	0.12	0.26	0.48	0.74	0.98	1.03	0.85	0.56	0.30	0.14	0.06	0.02	0.00	0.00	5.63	0.00
40	0.00	0.01	0.03	0.07	0.17	0.41	0.93	1.73	2.47	2.54	1.87	1.06	0.50	0.22	0.09	0.03	0.01	0.00	12.1	0.55
30	0.00	0.01	0.03	0.09	0.23	0.62	1.58	3.44	6.12	6.22	3.62	1.79	0.75	0.30	0.11	0.03	0.01	0.00	24.9	16.6
20	0.00	0.01	0.03	0.10	0.28	0.75	2.15	5.79	20.8	21.1	5.99	2.38	0.89	0.34	0.13	0.04	0.01	0.00	60.7	54.1
10	0.00	0.01	0.03	0.11	0.28	0.70	2.08	5.54	19.3	19.6	5.86	2.35	0.87	0.34	0.13	0.04	0.01	0.00	57.3	50.7
0	0.00	0.01	0.03	0.10	0.25	0.53	1.43	3.27	5.65	5.78	3.53	1.71	0.70	0.31	0.12	0.04	0.01	0.00	23.5	15.1
-10	0.00	0.01	0.03	0.08	0.20	0.37	0.75	1.53	2.34	2.43	1.79	1.00	0.51	0.25	0.10	0.03	0.00	0.00	11.4	0.36
-20	0.00	0.00	0.02	0.06	0.14	0.26	0.39	0.61	0.88	0.96	0.79	0.55	0.35	0.18	0.08	0.02	0.00	0.00	5.30	0.00
-30	0.00	0.00	0.01	0.04	0.09	0.16	0.24	0.31	0.34	0.37	0.35	0.29	0.20	0.11	0.05	0.02	0.00	0.00	2.61	0.00
-40	0.00	0.00	0.01	0.02	0.05	0.08	0.12	0.15	0.16	0.17	0.15	0.13	0.10	0.06	0.03	0.01	0.00	0.00	1.26	0.00
-50	0.00	0.00	0.00	0.01	0.02	0.03	0.05	0.06	0.07	0.08	0.08	0.06	0.05	0.03	0.01	0.00	0.00	0.00	0.57	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.03	0.03	0.03	0.02	0.02	0.01	0.00	0.00	0.00	0.00	0.19	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.00	0.06	0.28	0.83	2.00	4.48	10.7	23.9	60.0	61.1	25.7	12.4	5.57	2.50	1.00	0.31	0.05	0.00	211	---
Φ a	0.00	0.00	0.00	0.00	0.00	0.00	0.23	14.8	52.1	53.2	16.3	0.79	0.00	0.00	0.00	0.00	0.00	0.00	---	137

one-half-peak spread: U:8.2,D:9.1 , L:8.7,R:8.7


NEMA Beam Type: Type 3

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:24 January 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 96GRF1/315220W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 100 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:24 January 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: 96GRF1/315220W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 100 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25.3°C
Operators:
Test Date: 24 January 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.340m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25.3°C
Operators:
Test Date: 24 January 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.340m [K=1.0000]
Remarks:

AAI Figure

NAME: 96GRF1/315220W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 100 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 24 January 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.340m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF1/315220W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 100 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-85	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.01	0.03	0.02	0.02	0.03	0.05	0.05	0.04	0.06	0.08	0.07	0.06
-80	0.00	0.00	0.00	0.01	0.03	0.03	0.03	0.05	0.08	0.08	0.08	0.11	0.15	0.17	0.18	0.24	0.29	0.33	0.36
-75	0.00	0.00	0.00	0.03	0.06	0.07	0.07	0.11	0.15	0.18	0.23	0.33	0.44	0.53	0.59	0.67	0.75	0.82	0.88
-70	0.00	0.00	0.02	0.05	0.09	0.12	0.14	0.20	0.29	0.45	0.60	0.74	0.87	1.00	1.12	1.28	1.44	1.58	1.70
-65	0.00	0.00	0.03	0.08	0.13	0.19	0.27	0.45	0.70	0.96	1.16	1.35	1.57	1.77	1.94	2.12	2.30	2.43	2.51
-60	0.00	0.00	0.05	0.10	0.18	0.34	0.55	0.86	1.24	1.59	1.89	2.23	2.59	2.89	3.08	3.24	3.36	3.47	3.53
-55	0.00	0.01	0.06	0.13	0.30	0.55	0.88	1.32	1.82	2.32	2.83	3.35	3.81	4.23	4.62	4.94	5.09	5.26	5.39
-50	0.00	0.02	0.08	0.17	0.44	0.77	1.24	1.84	2.53	3.22	3.91	4.66	5.51	6.37	7.01	7.26	7.49	7.65	7.80
-45	0.00	0.02	0.09	0.24	0.57	1.00	1.63	2.45	3.33	4.13	5.13	6.46	7.68	8.98	9.83	10.5	10.8	11.1	11.5
-40	0.00	0.03	0.11	0.34	0.71	1.27	2.07	3.09	4.06	5.14	6.80	8.31	9.90	11.2	12.4	13.6	14.9	16.3	18.3
-35	0.00	0.03	0.13	0.43	0.86	1.53	2.53	3.71	4.80	6.46	8.46	10.4	12.0	13.7	16.1	19.0	23.9	28.6	30.7
-30	0.00	0.04	0.16	0.51	0.99	1.81	2.93	4.23	5.62	7.90	10.4	12.2	14.4	18.1	23.6	31.7	40.7	46.8	49.2
-25	0.00	0.04	0.18	0.57	1.13	2.05	3.26	4.65	6.51	9.31	11.9	14.4	18.5	25.6	36.8	50.6	64.5	76.3	81.4
-20	0.00	0.05	0.21	0.62	1.26	2.26	3.51	5.05	7.53	10.6	13.4	17.0	24.3	36.8	54.9	77.9	102	118	124
-15	0.00	0.05	0.23	0.67	1.35	2.41	3.70	5.47	8.38	11.5	14.8	20.1	31.4	50.3	77.6	111	142	174	187
-10	0.00	0.05	0.25	0.70	1.43	2.50	3.82	5.66	9.00	12.4	16.1	23.6	39.2	63.0	100	141	209	337	407
-5	0.00	0.05	0.26	0.72	1.47	2.54	3.88	5.68	9.31	13.1	17.1	26.8	44.8	73.4	115	172	344	687	885
0	0.00	0.05	0.27	0.73	1.49	2.53	3.85	5.56	9.35	13.4	17.7	29.2	47.4	78.9	122	189	440	918	1150
5	0.00	0.05	0.27	0.73	1.48	2.47	3.73	5.40	8.72	12.8	18.0	29.1	46.7	76.8	118	180	374	754	956
10	0.00	0.05	0.27	0.72	1.45	2.37	3.54	5.12	7.87	11.7	17.3	27.3	42.7	67.9	104	148	229	382	472
15	0.00	0.05	0.27	0.70	1.40	2.24	3.30	4.72	7.04	10.3	15.4	23.9	36.4	55.3	83.2	116	149	184	199
20	0.00	0.05	0.25	0.67	1.32	2.08	3.02	4.28	6.20	9.04	13.2	19.9	30.1	43.9	62.2	84.0	106	122	129
25	0.00	0.05	0.24	0.63	1.22	1.90	2.74	3.86	5.37	7.96	11.2	15.9	23.0	33.4	44.6	57.3	70.6	81.1	84.9
30	0.00	0.05	0.21	0.58	1.10	1.75	2.45	3.39	4.67	6.56	9.26	12.9	17.6	23.3	31.0	38.4	45.2	50.3	52.3
35	0.00	0.05	0.19	0.52	0.97	1.59	2.16	2.95	4.00	5.39	7.55	10.1	13.6	16.6	20.0	23.7	28.3	31.7	33.7
40	0.00	0.04	0.15	0.46	0.82	1.38	1.90	2.53	3.36	4.43	5.95	8.01	10.6	13.0	15.0	16.7	18.3	19.4	20.0
45	0.00	0.04	0.14	0.38	0.69	1.14	1.68	2.16	2.74	3.54	4.56	5.94	7.75	9.62	11.2	12.6	13.6	14.4	14.8
50	0.00	0.03	0.12	0.31	0.56	0.91	1.38	1.85	2.27	2.80	3.50	4.38	5.50	6.96	8.19	9.16	9.99	10.6	11.1
55	0.00	0.02	0.10	0.24	0.44	0.70	1.06	1.49	1.84	2.21	2.71	3.28	3.91	4.68	5.43	6.22	6.95	7.53	7.97
60	0.00	0.02	0.08	0.16	0.33	0.52	0.77	1.07	1.37	1.66	1.97	2.39	2.85	3.26	3.72	4.20	4.70	5.26	5.75
65	0.00	0.02	0.07	0.12	0.22	0.37	0.54	0.72	0.91	1.10	1.32	1.54	1.82	2.11	2.41	2.67	2.85	3.10	3.33
70	0.00	0.01	0.05	0.08	0.13	0.23	0.36	0.46	0.55	0.68	0.79	0.90	0.98	1.14	1.32	1.48	1.62	1.70	1.74
75	0.00	0.01	0.03	0.05	0.07	0.13	0.18	0.25	0.30	0.36	0.43	0.47	0.51	0.55	0.58	0.62	0.65	0.71	0.76
80	0.00	0.01	0.02	0.03	0.03	0.06	0.10	0.11	0.11	0.13	0.15	0.16	0.15	0.17	0.17	0.17	0.16	0.19	0.22
85	0.00	0.00	0.01	0.01	0.01	0.02	0.04	0.03	0.03	0.04	0.06	0.05	0.03	0.05	0.06	0.05	0.04	0.06	0.07
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: MEDIUM

Temperature:25.3°C

Operators:

Test Date:24 January 2023

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.340m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF1/315220W	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F 100 x 90	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-85	0.08	0.09	0.07	0.06	0.06	0.07	0.05	0.03	0.03	0.03	0.02	0.00	0.01	0.02	0.01	0.00	0.00	0.00	
-80	0.38	0.40	0.37	0.33	0.30	0.26	0.18	0.12	0.11	0.10	0.07	0.03	0.04	0.04	0.01	0.00	0.00	0.00	
-75	0.92	0.94	0.91	0.86	0.80	0.73	0.60	0.45	0.31	0.21	0.15	0.09	0.08	0.06	0.03	0.00	0.01	0.00	
-70	1.76	1.78	1.70	1.59	1.45	1.29	1.12	0.94	0.76	0.54	0.32	0.18	0.13	0.10	0.05	0.02	0.01	0.00	
-65	2.58	2.61	2.57	2.49	2.36	2.13	1.82	1.54	1.25	0.98	0.64	0.35	0.21	0.14	0.08	0.03	0.01	0.00	
-60	3.65	3.67	3.59	3.50	3.37	3.20	2.93	2.43	1.96	1.53	1.10	0.66	0.32	0.18	0.10	0.04	0.01	0.00	
-55	5.39	5.33	5.16	4.92	4.72	4.46	4.12	3.62	2.93	2.19	1.62	1.06	0.57	0.26	0.13	0.06	0.02	0.00	
-50	7.78	7.72	7.47	7.16	6.78	6.27	5.60	4.92	4.05	3.00	2.17	1.50	0.86	0.37	0.16	0.08	0.03	0.00	
-45	12.2	12.3	11.9	11.0	10.2	9.36	7.80	6.55	5.27	4.00	2.79	1.95	1.15	0.54	0.21	0.10	0.03	0.00	
-40	19.1	18.7	17.7	16.8	14.9	13.1	10.9	8.60	6.61	5.02	3.47	2.37	1.48	0.70	0.28	0.12	0.04	0.00	
-35	30.9	29.4	25.7	22.3	19.6	16.8	13.9	11.1	8.25	6.01	4.14	2.81	1.77	0.90	0.35	0.13	0.05	0.00	
-30	48.3	45.7	40.4	33.1	25.5	20.8	16.8	13.4	10.0	7.14	4.80	3.24	2.01	1.07	0.43	0.15	0.05	0.00	
-25	79.2	71.5	59.2	47.1	35.6	26.0	19.9	15.4	11.7	8.27	5.53	3.67	2.22	1.22	0.51	0.17	0.06	0.00	
-20	121	108	87.1	65.3	46.8	33.5	23.1	17.4	13.0	9.21	6.10	4.05	2.48	1.34	0.58	0.18	0.06	0.00	
-15	178	151	119	87.2	60.9	40.1	27.0	19.3	14.1	10.0	6.64	4.31	2.68	1.43	0.63	0.20	0.07	0.00	
-10	339	220	152	109	73.6	47.7	30.9	20.8	15.0	10.6	7.01	4.45	2.81	1.49	0.67	0.21	0.07	0.00	
-5	703	353	185	125	84.1	53.3	33.5	21.8	15.6	11.0	7.16	4.50	2.88	1.52	0.70	0.21	0.07	0.00	
0	932	440	200	131	89.2	54.8	34.6	22.2	15.9	11.0	7.12	4.47	2.89	1.51	0.72	0.22	0.08	0.00	
5	770	377	188	127	85.7	53.7	34.9	21.9	15.6	10.7	6.83	4.37	2.83	1.50	0.72	0.23	0.08	0.00	
10	390	233	155	111	75.7	50.4	32.8	20.9	14.9	10.1	6.39	4.18	2.72	1.46	0.71	0.23	0.08	0.00	
15	188	154	122	91.2	63.2	44.2	29.0	19.2	13.6	9.16	5.82	3.92	2.56	1.39	0.69	0.23	0.07	0.00	
20	125	111	90.8	67.7	49.7	35.7	24.1	16.9	11.7	7.95	5.21	3.60	2.36	1.30	0.66	0.22	0.07	0.00	
25	83.0	74.4	62.3	50.2	38.0	27.5	19.8	13.9	9.64	6.86	4.66	3.27	2.14	1.19	0.62	0.21	0.07	0.00	
30	52.3	49.1	43.1	35.2	27.2	21.0	15.3	11.1	7.92	5.81	4.06	2.93	1.92	1.07	0.57	0.20	0.06	0.00	
35	34.1	31.8	27.9	23.8	19.9	15.5	11.7	8.70	6.53	4.84	3.54	2.59	1.69	0.96	0.51	0.18	0.06	0.00	
40	20.2	19.8	18.7	17.1	14.4	11.4	8.79	6.85	5.31	4.03	3.07	2.26	1.45	0.82	0.44	0.15	0.05	0.00	
45	15.1	14.9	14.4	13.0	10.6	8.40	6.74	5.35	4.28	3.37	2.63	1.93	1.17	0.71	0.35	0.14	0.05	0.00	
50	11.3	11.2	10.7	9.19	7.62	6.28	5.14	4.24	3.46	2.80	2.23	1.54	0.95	0.59	0.27	0.12	0.04	0.00	
55	8.15	8.01	7.42	6.42	5.52	4.64	3.91	3.32	2.77	2.29	1.77	1.15	0.75	0.45	0.22	0.11	0.03	0.00	
60	5.73	5.55	5.10	4.56	3.95	3.43	2.96	2.52	2.18	1.69	1.21	0.85	0.57	0.32	0.15	0.09	0.03	0.00	
65	3.53	3.56	3.29	2.96	2.59	2.29	2.05	1.74	1.35	1.08	0.83	0.61	0.40	0.22	0.12	0.07	0.02	0.00	
70	1.72	1.67	1.62	1.52	1.39	1.24	1.14	0.99	0.84	0.68	0.55	0.41	0.24	0.13	0.09	0.05	0.02	0.00	
75	0.77	0.76	0.77	0.77	0.72	0.66	0.61	0.57	0.49	0.40	0.30	0.21	0.14	0.08	0.05	0.03	0.01	0.00	
80	0.21	0.21	0.25	0.28	0.27	0.25	0.25	0.22	0.18	0.15	0.13	0.10	0.07	0.03	0.02	0.02	0.01	0.00	
85	0.06	0.05	0.07	0.08	0.07	0.06	0.07	0.08	0.06	0.03	0.04	0.04	0.02	0.01	0.01	0.01	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: MEDIUM

Temperature:25.3°C

Operators:

Test Date:24 January 2023

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.340m [K=1.0000]

Remarks: