

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	4181.7 cd per klm.
(Luminaire orientation as tested.)	-2.0 degrees vertical
	-1.5 degrees horizontal

Beam Spread	At 10% of Imax	46.9V x 47.2H
	At 50% of Imax	14.5V x 14.8H
	At 90% of Imax	5.0V x 5.0H

Beam Flux	Total	780.6 lumens per klm.
	To 10% of Imax	539.8 lumens per klm.
	To 50% of Imax	156.2 lumens per klm.
	To 90% of Imax	35.9 lumens per klm.

Upward LOR	0.0 %
Downward LOR	78.1 %


Luminaire Efficiency (Light Output Ratio)	77.7 %
---	--------

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 06 October 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 96GRF2/130220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F44 x 72	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	96GRF2/130220	Imax (cd)	376.4
NOMINAL POWER (W)	1	AVAILABILITY (%)	53.5
RATED VOLTAGE (V)	220	Avai. FLUX (lm)	48.16
NOMINAL FLUX (lm)	90	LOR (%)	77.7
LAMPS INSIDE	1	TOTAL FLUX (lm)	69.89
TEST VOLTAGE (V)	220	θ @50% (H,V)	15,15DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00
90	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.08	0.00
80	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.16	0.00
70	0.00	0.00	0.00	0.01	0.01	0.02	0.03	0.04	0.04	0.04	0.03	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.29	0.00
60	0.00	0.00	0.00	0.01	0.02	0.04	0.06	0.09	0.11	0.11	0.09	0.06	0.03	0.02	0.01	0.00	0.00	0.00	0.65	0.00
50	0.00	0.00	0.00	0.01	0.02	0.04	0.06	0.09	0.11	0.11	0.09	0.06	0.03	0.02	0.01	0.00	0.00	0.00	1.91	0.00
40	0.00	0.00	0.01	0.01	0.03	0.07	0.15	0.31	0.42	0.41	0.27	0.13	0.06	0.03	0.01	0.01	0.00	0.00	4.39	0.35
30	0.00	0.00	0.01	0.02	0.05	0.13	0.43	0.74	0.92	0.90	0.68	0.35	0.11	0.04	0.01	0.01	0.00	0.00	8.26	5.62
20	0.00	0.00	0.01	0.02	0.07	0.26	0.75	1.31	1.92	1.84	1.19	0.63	0.19	0.05	0.02	0.01	0.00	0.00	17.0	15.0
10	0.00	0.00	0.01	0.02	0.08	0.37	1.00	2.19	5.54	4.80	1.85	0.81	0.26	0.06	0.02	0.01	0.00	0.00	20.0	18.0
0	0.00	0.00	0.01	0.02	0.08	0.37	1.06	2.48	7.03	5.77	1.98	0.81	0.25	0.06	0.02	0.01	0.00	0.00	9.96	7.82
-10	0.00	0.00	0.01	0.02	0.07	0.24	0.84	1.64	2.63	2.37	1.31	0.60	0.17	0.05	0.02	0.01	0.00	0.00	4.68	1.35
-20	0.00	0.00	0.01	0.01	0.04	0.13	0.38	0.85	1.13	1.04	0.66	0.26	0.10	0.03	0.01	0.01	0.00	0.00	1.48	0.00
-30	0.00	0.00	0.01	0.01	0.03	0.06	0.14	0.23	0.32	0.30	0.19	0.11	0.05	0.02	0.01	0.01	0.00	0.00	0.54	0.00
-40	0.00	0.00	0.00	0.01	0.01	0.03	0.05	0.08	0.10	0.09	0.07	0.04	0.02	0.02	0.01	0.00	0.00	0.00	0.23	0.00
-50	0.00	0.00	0.00	0.01	0.01	0.01	0.02	0.03	0.03	0.03	0.03	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.15	0.00
-60	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.08	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.02	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
HORIZONTAL (DEG)																				
Φ t	0.00	0.03	0.08	0.18	0.52	1.78	4.95	10.0	20.2	17.7	8.39	3.89	1.31	0.43	0.17	0.08	0.03	0.00	70	---
Φ a	0.00	0.00	0.00	0.00	0.00	0.00	1.32	7.56	18.0	15.4	5.62	0.30	0.00	0.00	0.00	0.00	0.00	0.00	---	48

one-half-peak spread: U:8.5,D:6.1 , L:8.5,R:6.5


NEMA Beam Type: Type 4

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:06 October 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 96GRF2/130220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F44 x 72	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 06 October 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: 96GRF2/130220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F44 x 72	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 06 October 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 06 October 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

AAI Figure

NAME: 96GRF2/130220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F44 x 72	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:
 Test Date:06 October 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.265m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF2/130220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F44 x 72	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.02	0.02	0.02	0.03	0.03	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.01
-85	0.02	0.03	0.03	0.03	0.05	0.04	0.03	0.05	0.06	0.06	0.05	0.07	0.08	0.07	0.06	0.07	0.09	0.08	0.06
-80	0.02	0.03	0.03	0.04	0.07	0.07	0.07	0.10	0.12	0.13	0.13	0.15	0.17	0.16	0.16	0.17	0.19	0.18	0.17
-75	0.02	0.03	0.03	0.06	0.10	0.11	0.12	0.16	0.19	0.21	0.21	0.24	0.27	0.28	0.28	0.30	0.32	0.32	0.30
-70	0.02	0.03	0.05	0.09	0.13	0.16	0.18	0.22	0.27	0.30	0.31	0.34	0.38	0.39	0.40	0.43	0.46	0.46	0.45
-65	0.02	0.03	0.06	0.11	0.17	0.21	0.24	0.28	0.34	0.38	0.39	0.42	0.47	0.50	0.51	0.53	0.57	0.57	0.57
-60	0.02	0.03	0.07	0.13	0.20	0.26	0.30	0.34	0.40	0.44	0.47	0.50	0.55	0.58	0.60	0.62	0.66	0.67	0.66
-55	0.02	0.04	0.09	0.16	0.23	0.31	0.35	0.39	0.45	0.51	0.54	0.57	0.63	0.69	0.71	0.75	0.78	0.80	0.80
-50	0.02	0.04	0.10	0.18	0.27	0.35	0.40	0.44	0.50	0.56	0.62	0.67	0.84	1.00	1.29	1.46	1.56	1.59	1.57
-45	0.02	0.05	0.12	0.20	0.29	0.38	0.44	0.49	0.55	0.63	0.76	1.11	1.43	1.72	2.14	2.50	2.73	2.84	2.85
-40	0.02	0.05	0.13	0.22	0.32	0.40	0.48	0.54	0.61	0.76	1.23	1.62	2.20	2.81	3.74	4.78	5.14	5.37	5.44
-35	0.02	0.06	0.14	0.24	0.34	0.42	0.51	0.60	0.69	1.21	1.66	2.41	3.29	5.08	6.10	7.21	8.30	8.85	8.86
-30	0.02	0.06	0.15	0.26	0.36	0.44	0.54	0.65	0.98	1.49	2.32	3.49	5.53	7.31	9.59	14.7	19.7	22.6	23.1
-25	0.02	0.07	0.16	0.27	0.37	0.46	0.56	0.70	1.29	1.90	3.24	5.24	7.41	11.4	21.9	30.1	35.4	37.2	36.6
-20	0.02	0.07	0.17	0.28	0.38	0.47	0.58	0.75	1.45	2.41	4.28	6.45	11.1	23.1	33.3	41.7	49.3	54.5	55.2
-15	0.02	0.07	0.18	0.29	0.39	0.49	0.61	0.95	1.67	2.93	4.97	7.92	19.1	31.1	41.3	54.9	70.8	85.4	87.0
-10	0.02	0.07	0.18	0.30	0.40	0.50	0.63	1.10	1.88	3.48	5.56	11.3	24.6	35.7	48.4	69.8	102	142	149
-5	0.02	0.07	0.18	0.30	0.40	0.51	0.63	1.19	2.00	3.77	5.93	14.3	27.1	37.9	53.4	82.4	143	251	301
0	0.02	0.07	0.18	0.30	0.40	0.51	0.64	1.21	2.04	3.82	6.07	15.7	27.4	37.8	53.9	83.7	141	299	374
5	0.02	0.07	0.19	0.31	0.41	0.51	0.64	1.20	2.02	3.69	5.86	15.0	25.9	35.6	49.3	73.5	109	188	227
10	0.02	0.07	0.19	0.31	0.41	0.52	0.65	1.13	1.91	3.38	5.37	12.5	23.3	32.0	42.0	57.8	78.0	95.7	99.3
15	0.02	0.07	0.18	0.31	0.41	0.51	0.64	1.01	1.73	2.90	4.64	8.60	19.7	27.1	34.1	43.7	53.9	62.2	64.6
20	0.02	0.07	0.18	0.30	0.40	0.51	0.62	0.87	1.51	2.48	4.03	6.28	15.0	21.8	27.7	32.8	38.7	42.1	43.1
25	0.02	0.07	0.18	0.29	0.39	0.49	0.59	0.78	1.34	2.12	3.26	4.70	8.55	16.8	21.0	25.0	27.8	29.8	30.4
30	0.02	0.07	0.17	0.28	0.38	0.46	0.55	0.66	1.13	1.65	2.50	3.73	5.06	8.65	14.9	18.3	20.1	21.5	21.8
35	0.02	0.07	0.16	0.27	0.36	0.43	0.51	0.62	0.90	1.36	1.94	2.73	3.73	4.68	6.36	10.2	13.1	14.8	15.1
40	0.02	0.06	0.15	0.25	0.33	0.40	0.47	0.57	0.69	1.09	1.45	1.98	2.59	3.30	3.98	4.57	5.26	5.68	5.71
45	0.02	0.06	0.14	0.23	0.30	0.37	0.44	0.53	0.62	0.71	1.15	1.41	1.75	2.22	2.63	3.03	3.35	3.56	3.64
50	0.02	0.05	0.13	0.20	0.27	0.33	0.41	0.49	0.55	0.61	0.70	1.02	1.27	1.45	1.62	1.85	2.02	2.11	2.10
55	0.02	0.05	0.11	0.18	0.23	0.29	0.36	0.44	0.49	0.53	0.61	0.69	0.75	0.97	1.16	1.24	1.26	1.29	1.32
60	0.02	0.04	0.10	0.15	0.19	0.25	0.32	0.38	0.42	0.47	0.53	0.58	0.61	0.65	0.71	0.74	0.74	0.76	0.79
65	0.02	0.04	0.09	0.12	0.15	0.21	0.27	0.31	0.34	0.39	0.45	0.49	0.51	0.54	0.58	0.59	0.59	0.60	0.62
70	0.02	0.04	0.07	0.09	0.11	0.16	0.21	0.24	0.27	0.30	0.35	0.38	0.39	0.42	0.46	0.46	0.46	0.47	0.48
75	0.02	0.04	0.06	0.07	0.08	0.11	0.15	0.17	0.19	0.22	0.25	0.27	0.28	0.30	0.33	0.32	0.31	0.33	0.34
80	0.02	0.03	0.05	0.05	0.05	0.07	0.10	0.11	0.11	0.13	0.16	0.16	0.16	0.18	0.20	0.19	0.18	0.20	0.21
85	0.02	0.03	0.04	0.04	0.03	0.04	0.06	0.05	0.05	0.06	0.08	0.07	0.06	0.08	0.09	0.08	0.07	0.08	0.09
90	0.02	0.03	0.03	0.03	0.02	0.03	0.03	0.03	0.02	0.03	0.03	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:06 October 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF2/130220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F44 x 72	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.01	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.01	
-85	0.07	0.08	0.07	0.05	0.06	0.07	0.05	0.04	0.04	0.05	0.03	0.01	0.02	0.03	0.01	0.00	0.01	0.01	
-80	0.18	0.19	0.17	0.15	0.16	0.16	0.13	0.11	0.11	0.10	0.07	0.05	0.05	0.05	0.02	0.01	0.01	0.01	
-75	0.32	0.32	0.30	0.27	0.27	0.26	0.23	0.20	0.19	0.17	0.13	0.10	0.09	0.08	0.04	0.01	0.01	0.01	
-70	0.46	0.45	0.43	0.40	0.40	0.38	0.34	0.31	0.29	0.26	0.20	0.16	0.13	0.10	0.06	0.02	0.02	0.01	
-65	0.58	0.59	0.57	0.55	0.55	0.52	0.46	0.41	0.38	0.34	0.28	0.22	0.18	0.14	0.08	0.03	0.02	0.01	
-60	0.68	0.68	0.66	0.65	0.65	0.63	0.58	0.55	0.49	0.41	0.34	0.29	0.24	0.17	0.10	0.05	0.03	0.01	
-55	0.82	0.82	0.78	0.76	0.75	0.71	0.67	0.64	0.60	0.52	0.41	0.35	0.29	0.21	0.13	0.06	0.03	0.01	
-50	1.52	1.44	1.31	1.17	0.95	0.81	0.76	0.72	0.67	0.60	0.51	0.42	0.34	0.24	0.15	0.08	0.04	0.01	
-45	2.71	2.47	2.15	1.79	1.42	1.21	0.91	0.80	0.72	0.65	0.59	0.49	0.38	0.28	0.17	0.09	0.04	0.01	
-40	5.12	4.61	3.89	3.03	2.31	1.71	1.30	0.99	0.79	0.70	0.64	0.57	0.42	0.31	0.19	0.11	0.05	0.01	
-35	8.30	7.37	6.16	5.07	3.68	2.59	1.79	1.29	0.91	0.77	0.69	0.60	0.46	0.33	0.22	0.12	0.05	0.01	
-30	20.3	16.1	11.0	7.63	5.74	3.93	2.59	1.70	1.22	0.85	0.73	0.63	0.50	0.35	0.24	0.14	0.06	0.01	
-25	33.8	29.6	23.1	14.7	8.26	5.70	3.78	2.29	1.40	0.98	0.77	0.65	0.54	0.37	0.26	0.15	0.06	0.01	
-20	50.1	41.4	32.2	25.0	14.8	7.65	5.10	3.06	1.76	1.18	0.80	0.67	0.55	0.40	0.28	0.16	0.06	0.01	
-15	76.6	59.0	43.4	31.0	22.5	11.6	6.15	3.93	2.12	1.31	0.86	0.69	0.57	0.42	0.29	0.17	0.07	0.01	
-10	118	82.8	56.1	37.9	26.5	16.2	7.38	4.57	2.42	1.41	0.92	0.71	0.59	0.44	0.30	0.17	0.07	0.01	
-5	190	103	66.5	42.9	28.5	19.3	8.34	4.87	2.62	1.49	0.97	0.73	0.60	0.45	0.31	0.18	0.07	0.01	
0	234	106	68.2	43.9	29.2	20.3	8.85	4.89	2.70	1.53	1.00	0.74	0.61	0.45	0.32	0.18	0.07	0.01	
5	149	91.5	62.1	41.7	28.5	20.0	8.88	4.83	2.66	1.51	1.01	0.73	0.60	0.45	0.31	0.18	0.07	0.01	
10	89.3	69.5	50.6	36.8	26.4	18.2	8.16	4.55	2.52	1.46	1.00	0.71	0.59	0.44	0.31	0.18	0.07	0.01	
15	59.6	49.9	39.9	30.2	22.8	14.9	6.42	4.08	2.32	1.37	0.93	0.70	0.58	0.43	0.30	0.17	0.07	0.01	
20	41.3	36.3	29.9	24.4	18.5	10.00	5.29	3.36	2.02	1.25	0.81	0.67	0.56	0.41	0.29	0.17	0.07	0.01	
25	29.5	26.4	22.9	18.8	12.3	6.37	4.30	2.71	1.62	1.14	0.75	0.64	0.54	0.39	0.28	0.16	0.07	0.01	
30	21.4	19.5	16.9	11.9	6.60	4.72	3.18	2.13	1.35	0.96	0.69	0.60	0.49	0.37	0.26	0.15	0.06	0.01	
35	14.4	11.8	8.12	5.84	4.49	3.36	2.35	1.56	1.18	0.77	0.65	0.55	0.45	0.34	0.24	0.14	0.06	0.01	
40	5.57	5.13	4.51	3.90	3.12	2.29	1.61	1.24	0.85	0.71	0.61	0.51	0.40	0.31	0.22	0.13	0.06	0.01	
45	3.57	3.29	2.85	2.42	1.92	1.49	1.24	0.84	0.72	0.64	0.56	0.46	0.35	0.27	0.20	0.12	0.05	0.01	
50	2.05	1.91	1.69	1.46	1.31	1.07	0.80	0.70	0.63	0.57	0.50	0.40	0.31	0.24	0.17	0.10	0.05	0.01	
55	1.26	1.20	1.14	1.01	0.85	0.73	0.68	0.61	0.54	0.50	0.43	0.34	0.26	0.20	0.14	0.09	0.04	0.01	
60	0.76	0.73	0.72	0.69	0.64	0.61	0.58	0.53	0.46	0.40	0.35	0.29	0.22	0.16	0.12	0.07	0.04	0.01	
65	0.60	0.58	0.58	0.57	0.53	0.50	0.48	0.42	0.35	0.31	0.28	0.24	0.17	0.12	0.09	0.06	0.03	0.01	
70	0.46	0.44	0.44	0.43	0.39	0.36	0.34	0.32	0.27	0.24	0.21	0.17	0.13	0.09	0.06	0.05	0.03	0.01	
75	0.32	0.30	0.31	0.31	0.28	0.25	0.24	0.23	0.19	0.15	0.14	0.12	0.09	0.05	0.04	0.04	0.02	0.01	
80	0.19	0.18	0.18	0.19	0.16	0.14	0.14	0.14	0.11	0.08	0.08	0.07	0.05	0.02	0.02	0.03	0.02	0.01	
85	0.08	0.06	0.07	0.08	0.06	0.05	0.06	0.06	0.04	0.03	0.03	0.04	0.02	0.01	0.01	0.02	0.01	0.01	
90	0.02	0.01	0.01	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.01	0.01	0.01	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:06 October 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks: